



British Manufacturing
since 1957



The Professionals Choice

UCCH1000

InstaTap Chilled Under Counter Water Dispenser



FULL SPECIFICATION



UCCH1000 InstaTap Chilled Under Counter Water Dispenser

Type	Under-counter chiller – <i>Push-button Dispenser</i>
Country of Design & Manufacture	UK
UNDER COUNTER UNIT:	
Electrical & Water Connections:	
Food Quality, flexible mains water hose	1.6 metres long (3/4" BSP)
Mains water pressure range	1 – 4 bar (15psi – 58psi)
Electrical Installation	UK standard 3-pin plug (5 amp)
Operating Parameters:	
Rated Voltage:	230V AC
Rated Current:	1.2A
Minimum ambient Temperature:	5°C
Maximum ambient Temperature:	30°C
Dimensions & Weights:	
Height:	390mm
Width:	180mm
Depth:	340mm
Weight (UC unit only) empty:	17.0kg
DISPENSE FONT:	
Dispense Font dimensions (W x D x H) mm	185 x 185 x 225
Tap font clearance mm	150
Dispense font construction:	304 grade Stainless Steel & chrome-plated Aluminium
Font interface with UC unit (electrical & water)	1.2 metre, plug-in XLR lead (electrical) and silicone rubber water transfer tube (water)
Performance (Chilled):	
180ml drinks per minute:	1 at 5°C
180ml drinks per minute:	2 at 7°C
1 st Litre Instantaneous:	6°C
2 nd Litre Instantaneous:	9°C
Litres/hour:	20 litres below 10°C
Filtration:	
In-line Filter (supplied)	Yes (not integral)
Filter Benefits:	Removes sediment & chlorine for fresh, clean tasting water
Max filter capacity:	5000 Litres
Mechanical sediment filtration:	5 micron
Standards & Approvals:	
WRAS approved	No (built to WRAS specification but not submitted)
Warranty & After-Sales:	
Guarantee	1 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)

VENTILATION & AIRFLOW:

IMPORTANT: The UCCH1000 Chilled Water Dispenser must be installed correctly and provide sufficient air-flow, ventilation and adequate expulsion of warm exhaust air. Ask for our installation information and recommendations and details of our ventilation kits.

Water Wizard Europe

T: 0161 696 8484

E: sales@waterwizardeurope.co.uk



Certificate Numbers: FM01234 & EM01234